

Aria Voice Recorder:

We develop a superior range of Voice Logger – **3002 Auto Answer with Mailbox** in accordance with the specific requirements of our clients. These are able to work as auto logger (automatically answer a call & record) and can operate on Windows 98/2000/XP/2003/NT. It supports three recorder modes, monitoring and DTMF/FSK incoming Caller ID, Support Incoming Caller ID Popup Milk.

Features:

- 365 different welcome greeting can be configured on each channel
- 2 Rate compress hardware, can recorder 70 hours/G HDD
- Consists of the incoming customer management system to recognize the incomers and the Popup Screen
- Support the simultaneous recording for the direct phone and extension
- Supports auto-backup, FTP back up the files onto the burning ROM, supports the auto fold repeat
- Alarm information displayed on the screen or in the e-mails when e meeting abnormal situation (cable broken)
- Support duple/quintuple/octuple compression and save and WAV format
- Support inquire, play and monitoring for the network
- With the default multi-language of Simplified Chinese/Traditional Chinese/ English / UAE, etc.

Requirement for the Hardware:

Suggested PC CPU:	More than P4 2.8G
Suggested Memory:	More than 512 MB
Suggested Hard Disk:	More than 40GB

USB 3002 USB BOX Tech Parameter:

Max installation for 1 PC	:Only support 1 piece box in 1 PC
Compress Rate	Hardware=2
Working Temperature	:5-40(Degree-c)
Power Consumption	:=15W
Humidity	:5%-85%
Storage Temperature	:-20?-70?
Voice Distortion Rate	:=2%
Voice Function	:WAV, VC2, VC5,AGC WAV, VD8,AGC
Module voltage resistance:	:250V WAV, VD8,AGC
Data Rate	:64KBPS?32KBPS?16KBPS

Data Transmission	Binary asynchronous serial
Codec	:HDB3 /AMI
Signal-To-Noise	:=30dB
Frequency Range	:>:300-3400Hz(±3dB)
Caller ID	:FSK?DTMF
DTMF Code	:0~9?*?#?A?B?C?D :300-3400Hz(±3dB)
FSK Modulate Mode	:Logical 0:2200Hz±1%
Input Impedance	:6000
Signal Monitor	:Signal sound,voice sound
Frame Structure	:CCITT G.704-1988
Clock and Data Recovering	:Complied to CCITT Rec.G.823-1988
Shaking limit: Complied to CCITT Rec.G.823,G.737,G.739,G.742-1988	
Phone Status Judge Voltage: 70-100V(Ring), 20-48V(Idle) , 5-17V(Hang up), 3.2V	